

## KITCHEN TYPE ROOF E.F. WITH PTC SENSOR

Rev.01  
27-05-2015



## GMC REF-547:

Roof fan with vertical outlet is applicable for industrial kitchen exhaust with medium temperatures up to 120°C

### Application

- Standard
- Kitchen

### Composition

- Outer casing made of seawater resistant AlMg3
- Motor outside of air stream
- Motor voltage controllable
- Swing out fan section
- Backward curved impeller
- Motor has a PTC sensor for thermic safety

### Order example

- REF-547: Mk.400 E4

400= Size  
E= 1x230V  
4= 1400rpm



HVAC Systems and Equipments Co.  
4640 Hedgcoxe Road 227 Plano, TX 75024 – US

[www.gmcair.com](http://www.gmcair.com)

# KITCHEN TYPE ROOF E.F. WITH PTC SENSOR

Rev.01  
27-05-2015



## Air performance data

Model	Qv [m3/h]										Note	
	0Pa	50Pa	100Pa	200Pa	300Pa	500Pa	700Pa	900Pa	1100Pa	1300Pa		
315 /250 - 4	2300	2150	1850	1300	-	-	-	-	-	-	-	
315 /250 - 6	1500	1200	650	-	-	-	-	-	-	-	-	
315/250 - 4/6	2300	2150	1850	1300	-	-	-	-	-	-	-	*
400/315 - 4	4700	4500	4250	3600	2950	-	-	-	-	-	-	
400/315 - 6	3100	2750	2200	-	-	-	-	-	-	-	-	
400/315 - 4/6	4700	4500	4250	3600	2950	-	-	-	-	-	-	*
400/315 - 4/8	4700	4500	4250	3600	2950	-	-	-	-	-	-	**
450/400 - 4	6700	6400	6100	5500	4600	2500	-	-	-	-	-	
450/400 - 6	4500	4000	3550	2250	-	-	-	-	-	-	-	
450/400 - 4/6	6700	6400	6100	5500	4600	2500	-	-	-	-	-	*
450/400 - 4/8	6700	6400	6100	5500	4600	2500	-	-	-	-	-	**
500/450 - 4	9100	8850	8500	8000	6700	5300	1000	-	-	-	-	
500/450 - 6	6100	5600	5050	3900	1000	-	-	-	-	-	-	
500/450 - 4/6	9100	8850	8500	8000	6700	5300	1000	-	-	-	-	*
500/450 - 4/8	9100	8850	8500	8000	6700	5300	1000	-	-	-	-	**
560/500 - 4	13300	13000	12500	12000	11000	9000	7000	2500	-	-	-	
560/500 - 6	8700	8100	7500	6200	4200	-	-	-	-	-	-	
560/500 - 4/6	13300	13000	12500	12000	11000	9000	7000	2500	-	-	-	*
560/500 - 4/8	13300	13000	12500	12000	11000	9000	7000	2500	-	-	-	**
630/560 - 4	19300	18750	18500	18000	16650	15250	13000	11000	6500	-	-	
630/560 - 6	12900	12000	11500	10500	8000	3500	-	-	-	-	-	
630/560 - 4/6	19300	18750	18500	18000	16650	15250	13000	11000	6500	-	-	*
630/560 - 4/8	19300	18750	18500	18000	16650	15250	13000	11000	6500	-	-	**
710/630 - 4S	23700	22500	22000	21500	21000	19000	17000	13750	11500	4000	-	
710/630 - 4	27500	27000	26500	26000	25000	23000	21500	18000	15000	3000	-	
710/630 - 6	18300	18000	17500	15500	14000	9000	-	-	-	-	-	
710/630 - 4/6	27500	27000	26500	26000	25000	23000	21500	18000	15000	3000	-	*
710/630 - 4/8	27500	27000	26500	26000	25000	23000	21500	18000	15000	3000	-	**
800/710 - 4	39500	39000	38500	38000	37000	35000	32500	29000	26500	24000	-	
800/710 - 6	26000	25500	24500	22000	21000	11500	11000	-	-	-	-	
800/710 - 4/6	39500	39000	38500	38000	37000	35000	32500	29000	26500	24000	-	*
800/710 - 4/8	39500	39000	38500	38000	37000	35000	32500	29000	26500	24000	-	**
900/800 - 6	37000	36000	35000	34000	32000	27500	23000	11300	-	-	-	
900/800 - 8	27500	26500	25000	23000	20000	12500	-	-	-	-	-	
900/800 - 6/8	37000	36000	35000	34000	32000	27500	23000	11300	-	-	-	***
1000/900 - 6S	43200	42500	41000	40000	37500	33000	28500	22000	13000	-	-	
1000/900 - 8S	32000	31000	30000	27000	25000	16000	-	-	-	-	-	
1000/900 - 6	52000	51000	50000	48000	45000	42000	37500	31500	24500	14000	-	
1000/900 - 8	38000	36750	35500	33000	30000	22500	8000	-	-	-	-	

\*Capacity at high speed. For the low speed, the given capacity value must be multiplied by 2/3, static pressure value must be multiplied with 4/9.  
 \*\*Capacity at high speed. For the low speed, the given capacity value must be multiplied by 1/2, static pressure value must be multiplied with 1/4.  
 \*\*\*Capacity at high speed. For the low speed, the given capacity value must be multiplied by 3/4, static pressure value must be multiplied with 9/16.

SC<sub>T</sub> = transformer controller  
 η<sub>t</sub> = maximum total efficiency  
 t<sub>m</sub> = maximum air temperature  
 t<sub>u</sub> = maximum ambient temperature  
 t<sub>o</sub> = minimum operating temperature  
 Lwa 2 = Casing sound power level  
 Lwa 5 = Sound power level @inlet  
 Lwa 6 = Sound power level @outlet  
 The sound power levels are measured according to DIN 45635 part 2 & 38

## Dimensions

Model	OD	B	E	H
315 /250 - 4	250	500	680	570
315 /250 - 6	250	500	680	570
315/250 - 4/6	250	500	680	570
400/315 - 4	315	560	780	640
400/315 - 6	315	560	780	640
400/315 - 4/6	315	560	780	640
400/315 - 4/8	315	560	780	640
450/400 - 4	400	630	880	690
450/400 - 6	400	630	880	690
450/400 - 4/6	400	630	880	690
450/400 - 4/8	400	630	880	690
500/450 - 4	450	710	980	730
500/450 - 6	450	710	980	730
500/450 - 4/6	450	710	980	730
500/450 - 4/8	450	710	980	730
560/500 - 4	500	800	1100	780
560/500 - 6	500	800	1100	780
560/500 - 4/6	500	800	1100	780
560/500 - 4/8	500	800	1100	780
630/560 - 4	560	900	1315	960
630/560 - 6	560	900	1315	960
630/560 - 4/6	560	900	1315	960
630/560 - 4/8	560	900	1315	960
710/630 - 4S	630	1000	1407	1060
710/630 - 4	630	1000	1407	1060
710/630 - 6	630	1000	1407	1060
710/630 - 4/6	630	1000	1407	1060
710/630 - 4/8	630	1000	1407	1060
800/710 - 4	710	1120	1612	1190
800/710 - 6	710	1120	1612	1190
800/710 - 4/6	710	1120	1612	1190
800/710 - 4/8	710	1120	1612	1190
900/800 - 6	800	1250	1785	1240
900/800 - 8	800	1250	1785	1240
900/800 - 6/8	800	1250	1785	1240
1000/900 - 6	900	1400	2002	1300
1000/900 - 8S	900	1400	2002	1300
1000/900 - 6	900	1400	2002	1300
1000/900 - 8	900	1400	2002	1300

