

CEILING & WALL TYPE DOMESTIC FAN

Rev.01
27-05-2015



GMC DMF-564:

Axial wall and ceiling fan

Application

- used for extraction of small rooms such as bathrooms and toilets
- Wall and ceiling mounting
- **The fans have a limited static pressure available (see diagram).**

Composition

- Body made of ABS
- 7 blade silent impeller
- Fastening by means of screws
- Supply: 230Vac 1ph
- Protection class IP34
- Available in 3 sizes: 100, 125 and 150 mm diameter

Models

- Range is available in three diameters; 100, 125 and 150 mm
- DMF-564: Standard model
- DMF-564, Mk.T: Model with timer 2-30 min.
- DMF-564, Mk.TH: Model with timer 2-30 min. and humidistat 50-90%RH

Text for tender

- The extraction of the bathroom shall be done by means of a wall mounted axial fan made of ABS connected to 150 mm duct. The fan shall be equipped with timer and humidity sensor.

Order example

DMF-564: Mk.125 DT

125= diameter
D= standard
DT= with timer



HVAC Systems and Equipments Co.
4640 Hedcoxe Road 227 Plano, TX 75024 – US

www.gmcair.com 

CEILING & WALL TYPE DOMESTIC FAN

Rev.01
27-05-2015



Technical data

DMF-564		Q _v (m ³ /h)	P (W)	n (rpm)	L _p @3m [dB(A)]
	100 D		98	14	2300
125 D		185	16	2400	40
150 D		335	30	2400	43

Notes

U = Voltage
P = Power
Q_v = Airflow rate
I = Current rate
n = speed
L_p = Sound level

