
## **SQUARE GRID GRILLES**





#### **GMC SGG-004 PRODUCT SPECIFICATIONS:**

- Standard Material: Aluminum profiles and Aluminum sheets.
- Usable for supply and return air ducts, have a useful decorative design.
- Both horizoantal and vertical blades are fixed to the frame.
- Has two models: 12 mm (SGG-104) and 20 mm (SGG-204) according to grid size between blades.
- On request, damper can be added to control air flow rate; Service panel can be added, also.
- Standard frame: Grilles with 22mm or 32mm.
- Eloxal, anodizing or electrostatic powder coating with the color from RAL catalogue.






### **SQUARE GRID GRILLES**




#### **TECHNICAL DETAILS**



#### **DATA DIAGRAMS**

#### SGG-004, PRESSURE LOSS AND NOISE LEVELS



Q [m³/h] [l/s] S [m²] v<sub>k</sub> [m/s]

∆p [Pa]

supply air flow rate effective outlet area velocity relating to the effective outlet area S total pressure loss



# **SQUARE GRID GRILLES**




### SGG-004, EFFECTIVE AREA TABLE (m<sup>2</sup>)

S (m²)	100	150	200	250	300	350	400	500	600	700	800	900	1000
100	0,005	0,008	0,012	0,015	0,018	0,022	0,025	0,031	0,037	0,044	0,051	0,056	0,063
150	0,008	0,013	0,019	0,023	0,028	0,034	0,038	0,049	0,058	0,069	0,079	0,088	0,099
200	0,012	0,019	0,028	0,034	0,041	0,050	0,057	0,072	0,086	0,101	0,117	0,131	0,146
250	0,015	0,023	0,034	0,043	0,051	0,062	0,07	0,09	0,107	0,126	0,146	0,162	0,182
300	0,018	0,028	0,041	0,051	0,061	0,074	0,084	0,108	0,128	0,151	0,174	0,194	0,217
350	0,022	0,034	0,050	0,062	0,074	0,091	0,103	0,131	0,155	0,184	0,212	0,236	0,265
400	0,025	0,038	0,057	0,070	0,084	0,103	0,116	0,149	0,176	0,208	0,241	0,268	0,3
450	0,027	0,043	0,063	0,079	0,094	0,115	0,130	0,166	0,197	0,233	0,269	0,300	0,336
500	0,031	0,049	0,072	0,090	0,108	0,131	0,149	0,19	0,225	0,266	0,307	0,342	0,383
550	0,034	0,053	0,079	0,098	0,118	0,143	0,162	0,207	0,246	0,291	0,336	0,374	0,419
600	0,037	0,058	0,086	0,107	0,128	0,155	0,176	0,225	0,267	0,315	0,364	0,406	0,454


### MOUNTING DETAILS

- 1. Screw Mounting Detail
- 2. Clip Mounting Detail
- 3. Plenum Box Dimensions



B (mm)	H (mm)							
	100	150	200	300				
200	ø80							
250	ø100	ø125						
300	ø125	ø160	ø200					
400	ø125	ø160	ø200					
500	ø125	ø160	ø200					
600	600	ø160	2 x ø200	ø250				
800	800			2 x ø250				
1000	1000			2 x ø250				

### 4. Plenum Box Mounting Detail







# Rev.02 26-05-2015


# **SQUARE GRID GRILLES**

### 5. Ceiling Mounting

- a. Drywall Mounting Detail
- b. Suspended Roof Mounting Detail
- c. Clip-in Mounting Detail









# Rev.02 26-05-2015

# **SQUARE GRID GRILLES**

#### **ORDER PARAMETERS**

SGG-004	PL	22	PFD	OD9010	SM	N 40	00X400	
SGG-104:								
12mm grid								
SGG-204:							N: Neck Size	
20mm grid	20mm grid						F: Frame Size	
00: No Accessory						00: No Mounting		
FL: with Filter						BF: Blind Frame		
PL: with Plenum Box						SM: Screw Mounting		
22: Frame=22mm					CM: Clips Mounting			
32: Frame=32mm								
000: Without Damper				00: No coating				
OFD: Opposite Flap Damper				EX: Eloxal Coating				
PFD: Parallel Flap D		OD: Oven Drying Coating						

