



Aluminum Punkah Louver -Round Reducer Series



HIGH VELOCITY TASK AIR OUTLET

- Low Noise Levels
- Low Pressure Requirements

ADJUSTABILITY

- Easy Finger Tip Adjustment
- Directional Air Pattern Control:
70 Degree Global Rotation Minimum
±35 Degree Deflection
360 Degree Rotation

INSTALLATION

- Mounts Cleanly to Exposed Ductwork

MODEL	SIZE	A	B	C	D	F	H
APL-06/06A-RR	6	3	5-9/16	1	6	8	6-9/16
APL-08/08A-RR	8	4-3/8	6-3/4	1	8	10	7-3/4
APL-10/10A-RR	10	5-3/4	8	1	10	12	9
APL-12/12A-RR	12	7-3/8	8-1/2	1	12	14	9-1/2
APL-14/14A-RR	14	8-5/8	9-5/8	1-5/8	14	16	11-1/4
APL-16/16A-RR	16	9-3/4	10-3/4	2-1/4	16	18	13
APL-18/18A-RR	18	10-1/2	12	1-3/4	18	20	13-3/4
APL-20/20A-RR	20	12-3/8	13-3/8	2-3/8	20	22	15-3/4

Inches measured to the nearest 1/16 inch

STANDARD FINISH:

- #10 Clear Anodized
- #42 Gloss Black Powder Coat
- #52 White Powder Coat
- #72 Silver Metallic Powder Coat
- #00 Mill Aluminum

OPTIONS:

- Aperture Damper
- Custom Finish _____

MATERIAL:

- Aluminum
- Stainless Steel Damper Hardware

NOTES:

- Frame Slides Cleanly Into End of Exposed Ductwork
- Mounting Screws Included
- "A" in Model Name Designates Aperture Damper Required

Project:	<h2>APL Series</h2> <p>Aluminum Punkah Louver - Round Reducer Series</p>	
Architect:		
Engineer:		
Contractor:	Form No: 20014S	
Submitted By:	Date:	Drawn By: MH January 2005